

AMERICAN INTERNATIONAL INDUSTRIES

Safety Data Sheet Ardell Duralash Starter Kit (Lashtite Clear)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

Product identifier

Product name Ardell Duralash Starter Kit (Lashtite Clear)

Product number 87-2564, 87-3221, 130131, 65058 found in kit 30550, 240462, 65061

Other means of identification

Uses:

Eyelash Adhesive

Details of the supplier of the safety data sheet

Name American International Industries

Address 2220 Gaspar Ave

Los Angeles, CA 90040

USA

Telephone 323-728-2999

Emergency telephone number

Chem-Tel: 1(800) 255-3924

SECTION 2: Hazards identification

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 (CLP)

- Eye damage/irritation (chapter 3.3), Cat. 2A, H319
- Flammable liquids (chapter 2.6), Cat. 2, H225

For the full text corresponding to the "H"-codes displayed in this section, refer to Section 16.

Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP]

Hazard pictograms



Signal word Danger

Hazard statement(s)

H319 Causes serious eye irritation H225 Highly flammable liquid and vapor

Precautionary statement(s)

P264 Wash hand thoroughly after handling. P102 Keep out of reach of Children

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for 20 minutes. Remove contact

lenses if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P210 Keep away from heat, hot surfaces, sparks, open flames, and other ignition

sources. No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse

skin with water/shower.

P403+P235 Store in a well ventilated place. Keep cool.

SECTION 3: Composition/information on ingredients

Mixtures

Components

Component	Concentration
Methoxyisopropyl Acetate (CAS no.: 108-65-6; EC no.: 203-603-9; Index no.: 607-195-00-7	35 - 45 %
CLASSIFICATIONS: Flammable liquids (chapter 2.6), Cat. 3; Eye damage/irritation (chapter 3.3), Cat. 2. HAZARDS: H226 - Flammable	
liquid and vapor; H319 - Causes serious eye irritation.	
Nitrocellulose (CAS no.: 9004-70-0)	25 - 35 %
CLASSIFICATIONS: Not classified HAZARDS: Non hazardous.	
Alcohol Denat. (CAS no.: 64-17-5; EC no.: 200-578-6; Index no.: 603-002-00-5)	25 - 35 %
CLASSIFICATIONS: Flammable liquids (chapter 2.6), Cat. 2. HAZARDS: H225 - Highly flammable liquid and vapor.	

SECTION 4: First aid measures

Description of first aid measures

General notes Though this product is non hazardous for its indented use, in all cases, if

symptoms persists contact a physician.

Following inhalation If breathed in, move person into fresh air. If not breathing, give artificial

respiration. Consult a physician.

Following skin contact Rinse with plenty of water. Get medical attention if irritation develops and

persists.

Following eye contact Rinse thoroughly with plenty of water for at least 15 minutes. Get medical

attention if symptoms occur.

Following ingestion Get medical attention immediately. If swallowed, do NOT induce vomiting.

Contact a physician or a poison control center immediately. Never give

anything by mouth to an unconscious person.

Self-protection of the first aider

Use personal protective equipment.

Most important symptoms and effects, both acute and delayed

If inhaled for long periods of time, can cause dizziness/drowsiness, headache and nausea.

SECTION 5: Firefighting measures

Extinguishing media

Dry chemical, carbon dioxide, Halon foam. Water may be ineffective. Water spray may be used to keep fire exposed containers cool and to disperse vapors.

Special hazards arising from the substance or mixture

Vapors can travel to a source of ignition and flashback. "Empty" containers retain product residue (liquid and/or vapor) and can be dangerous. Empty drums should be completely drained, properly bunged and promptly returned to a drum reconditioner, or properly disposed of.

Advice for firefighters

First responders should wear eye protection. Structural fire-fighters must wear MSHA/NIOSH approved SCBA and full protective equipment. Use a water spray or fog to reduce vapors. Water may not be effective in extinguishing a fire involving this product.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Household: Absorb with inert material and place in a appropriate waste disposal

Industrial: Avoid contact with skin, eyes, and clothing. Remove all sources of ignition. Absorb with an inert material and put the spilled material in an appropriate waste disposal. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through the sanitary system

Environmental precautions

Household: Do not place spilled product in any drain or water system that can go into the environment. Industrial: Should not be released into the environment.

Methods and material for containment and cleaning up

Highway or railway spills call chemtrec (800) 424-9600 cont. U.S. Collect (202) 483-7616 from Alaska and Hawaii. Stay upwind and away from spill. Keep all sources of ignition and hot metal surfaces away from spill. Keep out of drains, sewers, or waterways. Use sand or other inert material to dam and contain spill. Do not flush with water; use absorbent pads. For large spills call response team and notify appropriate state/local agencies. Immediately notify the National Response Center (phone number: 800-424-8802) in case if the spill is in excess of EPA reportable quantity.

Version: 1.0, Date of issue: 2017-12-12, p. 3 of 7

SECTION 7: Handling and storage

Precautions for safe handling

Avoid prolonged contact with the product. After use, wash hands and exposed skin with soap and water. Do not eat, drink, or smoke while handling this product.

Conditions for safe storage, including any incompatibilities

Keep this material away from heat, sparks, and open flame. Open containers slowly on a stable surface. Keep container closed tightly when not in use. Empty containers may contain residual amounts of the product; therefore handle empty container with care.

Store containers in a cool dry place, away from direct sunlight, other light sources, or any intense heat. Store away from incompatible materials as appropriate.

SECTION 8: Exposure controls/personal protection

Control parameters

CAS: 64-17-5

Ethyl alcohol (Ethanol)

Cal/OSHA: 1000 ppm PEL inhalation; NIOSH: 1000 ppm REL inhalation; OSHA: 1000 ppm PEL inhalation; 1900 mg/m3 PEL inhalation

Exposure controls

Appropriate engineering controls

Distribution, Workplace and Household Settings: Ensure adequate ventilation. Product Manufacturing Plant (needed at Product-Producing Plant ONLY): Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Personal protection equipment

Eye and face protection

Depending on the use of this product splash or safety glasses may be worn in an industrial setting. When necessary refer to U.S. OSHA 29 CFR §1910.133, Canadian standards, or the European standard EN166.

Skin protection

Skin Protection: None required with normal household use. Industrial Setting: Protective gloves (for hands) and protective clothing are required where repeated or prolonged skin contact may occur.

Body protection

No special body protection is required for this product under typical use and handling.

Respiratory protection

No respiratory protection is required under typical circumstances of use and handling. If necessary, use only respiratory protection authorized by U.S. OSHA 29 CFR §1920.134, or applicable U.S. local state regulations.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance Viscous Liquid/ Colorless

Odour Characteristic
Odour threshold No data available.

pH No data available.

Melting point / freezing point No data available.

Initial boiling point and boiling range 77 C (171 F) - 338 (640 F)

Flash point 12.2 C (54 F)
Evaporation rate No data available.
Flammability (solid, gas) Flammable

Upper/lower flammability limits

No data available.

8 8 C (172.4 F)

VOC 30%

Vapour pressure

Vapour density

No data available.

No data available.

No data available.

No data available.

Solubilit(ies) Slightly

Partition coefficient: n-octanol/water

Auto-ignition temperature

Decomposition temperature

Viscosity

No data available.

No data available.

No data available.

1.000 – 4,000

Explosive properties

Oxidizing properties

No data available.

No data available.

Specific gravity

0.970 – 0.990

SECTION 10: Stability and reactivity

Reactivity

No data available

Chemical stability

Stable under recommended storage conditions.

Incompatible materials

Acids, Alkalies, and Peroxides

Hazardous decomposition products

If exposed to extremely high temperatures, the products of decomposition may include irritating vapors and carbon oxide gases (e.g. CO2, CO).

SECTION 11: Toxicological information

Acute toxicity

Vapors may cause drowsiness and dizziness.

Skin corrosion/irritation

Causes skin irritation and exposure to the skin can cause dermatitis.

Serious eye damage/irritation

May be irritating to eyes

Germ cell mutagenicity

No data available.

Carcinogenicity

No data available.

Reproductive toxicity

No data available.

STOT-single exposure

May cause respiratory irritation

STOT-repeated exposure

No data available.

Aspiration hazard

No data available.

SECTION 12: Ecological information

Toxicity

Do not let product enter drains.

Persistence and degradability

No data available.

Bioaccumulative potential

No data available.

Mobility in soil

No data available.

SECTION 13: Disposal considerations

Waste treatment methods

Disposal of the product

Dispose of in accordance with federal, state and local regulations.

SECTION 14: Transport information

DOT (US)

UN Number: 1993

Class: 3

Packing Group: II

Proper Shipping Name: Flammable liquid, n.o.s (Methoxyisopropyl Acetate, Ethanol)

IMDG

UN Number: 1993

Class: 3

Packing Group: II

Proper Shipping Name: Flammable liquid, n.o.s (Methoxyisopropyl Acetate, Ethanol,)

IATA

UN ID: ID8000 Class: 9

Class. 9

Packing Instructions:Y963

Proper Shipping Name: Consumer Commodity

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

New Jersey Right To Know Components

Common name: NITROCELLULOSE

CAS number: 9004-70-0

Pennsylvania Right To Know Components

Chemical name: Cellulose, nitrate

CAS number: 9004-70-0

New Jersey Right To Know Components

Common name: ETHYL ALCOHOL

CAS number: 64-17-5

Pennsylvania Right To Know Components

Chemical name: Ethanol CAS number: 64-17-5

Toxic Substances Control Act (TSCA) Inventory

The components of this product are TSCA listed

WHMIS

B2 – Flammable Liquid D2B –Toxic – Other

Included for disclosure on the IDL at 0.1% or greater Alcohol Denat. (Ethanol)

SECTION 16: Other information

Full text of hazard statements referenced in Section 2

H225 Highly flammable liquid and vapor H319 Causes serious eye irritation

Further information/disclaimer

This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR § 1910.1200 and GHS. To the best of A.I.I.'s knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness is not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.