PRODUCT NAME: Cuccio Colour Veneer- Fuse

This form is regarded to be in compliance with 29 CFR Part 1910.1200

SECTION 1 : IDENTIFICATION

.....

PRODUCT NAME: Cuccio Colour Veneer- Fuse

Product Use: Adhesion Improvement

Manufacturer's Name: Star Nail International, Inc. Chemical Family: Nail Primer

29120 Avenue Paine Address: **Proprietary Mix**

City, State, Zip: Valencia, CA 91355 CAS# N/A

Preparation Date of SDS: 08/19/2015

24 HR. EMERGENCY TELEPHONE: CHEMTEL 1-813-248-0573

SECTION 2: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

This information may be based on findings from

related or similar materials.

- May cause eye irritation.
- Flammable liquid and vapor!
- May cause skin irritation.
- Avoid prolonged or repeated breathing of gases, vapors or mists.
- Unstable (reactive) upon depletion of inhibitor. This is only a slight risk.
- May be absorbed through the skin.

Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry Inhalation, skin contact, eye contact

> Exposure causes eye irritation. Symptoms include stinging, tearing, redness and swelling. Eves: Skin: Can cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may

include

redness, burning, drying, cracking, and skin burns.

Ingestion: Swallowing small amounts during normal handling is not likely to cause harmful effects;

swallowing large amounts may be harmful. This material can get into the lungs during

or vomiting. swallowing

Inhalation: Vapor and mist are irritating to mucous membranes. Breathing small amounts during normal

handling is not likely to cause harmful effects. Breathing large amounts may be harmful.

Symptoms usually occur at air concentrations higher than the recommended exposure limits.

Sub-Chronic Effects: May cause headaches, nausea, vomiting and narcotic effect if over-exposed.

Chronic Health Effects:

(Long-term) No appropriate human or animal health effects data are known to exist.

NOTE: Refer to Section 11, Toxicological Information for Details

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.



Date: August 19, 2015



PRODUCT NAME: Cuccio Colour Veneer- Fuse Date: August 19, 2015

.....

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

| CAS# | EINECS# | INCI Name | Exposure | Limits | Carcinogen |
|---------------|----------------------------------------|-----------------------------------------------|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| | | TW | OSHA A/STEL | | H C/NTP/OSHA |
| 141 - 78 - 6 | 205-500-4 | Ethyl Acetate | 400 ppm | 400 pp | m Not |
| 1565-94-2 | 216-367-7 | bisoxyhydroxypropy | I | N/E | Not |
| late 868-77-9 | 212-782-2 | НЕМА | N/E | N/E | Not |
| , | | * See secti | on 16 | | |
| | 141 - 78 - 6 1565-94-2 late 868-77-9 | 141 - 78 - 6 205-500-4 1565-94-2 216-367-7 | TW 141 - 78 - 6 | OSHA TWA/STEL 141 - 78 - 6 205-500-4 Ethyl Acetate 400 ppm 1565-94-2 216-367-7 Isopropylidenediphenyl N/E bisoxyhydroxypropyl methacrylate late 868-77-9 212-782-2 HEMA N/E N/DA - No Data Available * See section 16 | OSHA TWA/STEL TWA/STEL 1ARC 141 - 78 - 6 205-500-4 Ethyl Acetate 400 ppm 400 pp. 1565-94-2 216-367-7 Isopropylidenediphenyl N/E N/E bisoxyhydroxypropyl methacrylate late 868-77-9 212-782-2 HEMA N/E N/E N/DA - No Data Available * See section 16 |

Ethyl Acetate: Hazard Symbol - F, Xi Risk Phrases - R11, R36, R66, R67 Safety Phrases - S2, S16, S26, S33

2,2-bis-(4-(2-hydroxy-3-methacryloxypropoxy)BIS-GMA: Hazard Symbols - N/E Risk Phrases - N/E Safety Phrases - N/E

2-Hydroxy ethyl methacrylate: Hazard Symbols - Xi Risk Phrases - R36/38, R43 Safety Phrases - S2, S26, S28

See Section 16 for Risk and Safety Phrase Key

SECTION 4: FIRST AID MEASURES

First Aid for Eye: If symptoms develop, move individual away from exposure and into fresh air. Flush eyes gently for 15 min. with water while holding eyelids apart. If symptoms persist or there is any visual difficulty, seek

medical

attention.

First Aid for Skin: Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention.

First Aid for Inhalation: Remove to fresh air. If breathing is difficult, administer oxygen. If symptoms persist, seek medical attention.

First Aid for Ingestion: If individual is drowsy or unconscious, do not give anything by mouth; place individual on the leftside with the head down. Seek medical attention for advice about whether to induce vomiting. If

possible, do not leave individual unattended.

SECTION 5: FIRE FIGHTING MEASURES

| Flash Point (°F/°C) | Flammable Limit (vol%) | Auto Ignition Temperature (vol%) |
|---------------------------|---------------------------|----------------------------------|
| TAG Closed: 26°F / -3.3°C | 400 ppm | 750 ° F - 900 ° F |

The above information may be based in part on information provided by component suppliers and is believed to be correct hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied r accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

PRODUCT NAME: Cuccio Colour Veneer- Fuse

Method:

Extinguishing Media: Foam, dry chemical, cold water spray.

Fire Fighting

Instructions: Wear self-contained breathing apparatus and protective clothing. USE WATER WITH

CAUTION. Water spray may be used to keep fire-exposed containers cool. Water may be

ineffective in fighting the fire. Fight fire from a safe distance and protected location.

Unusual Hazards: Flammable. When exposed to heat and flame, material is a fire explosion hazard. It may produce toxic

products CO, carbon dioxide. Vapors may cause a flash fire or ignite explosively. Vapors may travel a considerable distance to a source of ignition and flash back. Prevent buildup of vapors

Date: August 19, 2015

or gases to explosive concentrations.

SECTION 6: ACCIDENTAL RELEASE MEASURES

.....

Spill or Release

Eliminate all sources of heat and ignition. Use absorbent material for spills and dike it, wash spill material Procedures:

> into retaining containers. Place containers in a well ventilated area. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g.,

> vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials,

such as saw dust. Do not flush to sewer! US Regulations (CERCLA) require reporting spills and releases

to

soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard

National

vapors, to

Response Center is (800) 424-8802. If a leak or spill has not ignited, use water spray to disperse the

protect personnel attempting to stop leak, and to flush spills away from exposures.

SECTION 7: HANDLING AND STORAGE

Handling: Keep containers cool and dry. Keep away from heat, light and ignition sources. Avoid breathing

high vapor concentrations. Avoid prolonged or repeated contact with skin. Use only with

adequate ventilation. Wash skin thoroughly after handling.

Store in a well ventilated area. Store @ 70 + 15 ° F, allow some air space above liquid level. Keep Storage:

containers closed while not in use.

Explosion Hazard: Vapors are heavier than air and may travel along the ground or may be moved by ventilation and

ignited by pilot lights, other flames, sparks, heaters, smoking or other ignition sources at locations

distant from material handling point. Never use welding or cutting torch on or near drum (even

empty)

because product (even just residue) can ignite explosively.

SECTION 8: EXPOSURE CONTROLS/ PERSONAL PROTECTION

Engineering Controls: Facilities storing or utilizing this material should be equipped with an eye facility and safety shower.

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

PRODUCT NAME: Cuccio Colour Veneer- Fuse

cio Colour Veneer- Fuse

Date: August 19, 2015

Use process enclosures local exhaust ventilation, or other engineering controls to control

airborne

levels below recommended exposure limits. Use explosion-proof ventilation equipment.

Personal Protective Equipment

General: To identify additional Personal Protective Equipment (PPE) requirements, it is recommended that a

hazard assessment in accordance with the OSHA PPE Standard (29CFR1910.132), or European Standard EN166 be conducted before using this product . Provide eye wash stations and safety showers. Wear impervious clothing to prevent ANY contact with this product, such as gloves, apron, boots, or whole

body suit. Nitrile rubber is better than PVC.

Eye/ Face Protection: Chemical splash goggles in compliance with OSHA regulations are advised; however, OSHA

regulations also permit other type of safety glasses.

Skin Protection: Wear resistant gloves. To prevent repeated or prolonged skin contact, wear impervious clothing and

boots.

Respiratory Protection: A NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be

permissible under certain limited circumstances where airborne concentrations are expected to

exceed

exposure limits. Protection provided by air purifying respirators is limited. Wear a

NIOSH/MSHA or

European Standard EN 149 approved full-face piece airline respirator in the positive pressure

mode with

emergency escape provisions. Follow OSHA respirator regulations found in 29 CFR 1910.134 or

European Standard EN 149.

SECTION 9:

| Appearance | Odor & Odor Threshhold | рН | VOC (g/L) | Specific Gravity | Viscosity | % Volatile |
|--------------|------------------------|-----|--------------|------------------|-----------|-------------|
| Clear Liquid | ester like odor | N/A | 736 | (H2O=1):0.92 | 15 cps | W/W % : 50+ |

| | Decomposition Temperature | Octanol/Water Partitioning Coefficient Log Po/w | Vapor Pressure: | Vapor Density | Evaporation Rate | Ignition | Solubility In Water (20°C) |
|------|------------------------------|-------------------------------------------------|--------------------|------------------|---------------------|----------|----------------------------------|
| N/DA | N/DA | N/DA | N/DA | (Air=1):1 | NA | NA | Insoluble |

| Flash Point (°F/°C) | Flammable Limit (vol%) | Auto Ignition Temperature (vol%) |
|---------------------------|---------------------------|----------------------------------|
| TAG Closed: 26°F / -3.3°C | 400 ppm | 750 ° F - 900 ° F |

SECTION 10:

Stability: Incompatibility (Materials to Avoid):
Stable Avoid oxidizing agents, acids & bases (heat)

Hazardous Decomposition Products: Hazardous Polymerization:

Heated material produces NO2, CO2, CO May occur

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

PRODUCT NAME: Cuccio Colour Veneer- Fuse

Conditions to Avoid: Heat, flame, ignition sources.

SECTION 11: TOXICOLOGICAL INFORMATION

| Acute Oral Toxicity | Acute Dermal Toxicity | Acute Inhalation Toxicity | Irritation – Skin | Irritation-Eye |
|-------------------------------|--------------------------------|----------------------------------------------------|-------------------|-----------------|
| Oral LD50 (rat) : 4.0-6.0g/kg | Dermal LD50 (rabbit): >20mL/kg | Inhalation LC50 (rat) : 3500 - 8000 ppm/4 hours | Rabbit : slight | Rabbit : slight |

Date: August 19, 2015

Since this product contains a very low concentration of active components, the primary toxicological information is derived from the oligomers. Further hazardous properties cannot be excluded. The product should be handled with care when dealing with chemicals

| Sensitization | Mutagenicity | Sub-chronic Toxicity |
|---------------|-----------------------------|----------------------|
| N/DA | E.Coli: DNA Damage: 20mol/L | N/DA |

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicological Information

| Acute Toxicity to fish | Acute Toxicity to Invertebrates | Acute Toxicity to Algae | Bioconcentration | Toxicity to Sewage Bacteria |
|---------------------------|---------------------------------|----------------------------|------------------|--------------------------------|
| N/DA | N/DA | N/DA | N/DA | N/DA |

Chemical Fate Information

| Biodegradability | N/DA | |
|------------------------|------|--|
| Chemical Oxygen Demand | N/DA | |

To the best of our knowledge, the ecotoxocological and chemical fate properties have not been thoroughly investigated. Do not allow to enter drinking water supplies, wastewater, or soil

SECTION 13: DISPOSAL CONSIDERATIONS

Dispose of diking materials and absorbent in compliance with State, Local, and Federal regulations. Residual vapors may explode on ignition; do not cut, drill, or weld on or near the container. Mix with compatible chemical which is less flammable and incinerate. Whatever cannot be saved for recovery or recycling should be handled as hazardous waste and sent to a RCRA approved waste facility. Processing, use or contamination of this product may change the waste management options. State and local disposal regulations may differ from federal disposal regulations. Dispose with federal, state and local requirements. For EU Member of container and unused contents in accordance refer to any relevant Community provisions relating to waste. In their absence, it is useful to remind the

States, please user that national or regional provisions may be in force.

SECTION 14: TRANSPORTATION INFORMATION

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

PRODUCT NAME: Cuccio Colour Veneer- Fuse Date: August 19, 2015

| Date: August 15, 2015 | | |
|--------------------------|---------------------------------------------------------------------------------------------------------|--|
| | | |
| | | |
| UN1993, Flammable liquid | ds, n.o.s., (ethyl acetate), 3, PGII | |
| UN1993 | | |
| No | | |
| T8,T31 | | |
| 128 | | |
| | | |
| | | |
| UN1993, Flammable liquid | ds, n.o.s., (ethyl acetate), 3, PGII | |
| 3 | | |
| UN1993 | | |
| A3 | | |
| 3L | | |
| | | |
| | | |
| UN1993, Flammable liquid | ds, n.o.s., (ethyl acetate), 3, PGII | |
| 3.2 | | |
| UN1993 | | |
| None | | |
| 307 | | |
| | UN1993 No T8,T31 128 UN1993, Flammable liquid 3 UN1993 A3 3L UN1993, Flammable liquid 3.2 UN1993 None | |

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

| US Federal Regulations | · |
|-------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Clean Air Act: HAP/ODS | This product contains the following hazardous air pollutants (HAP), as defined by the U. S. Clean Air Act: NONE This product contains no ODS's |
| Clean Water Act: Priority Pollutant | This product contains the following chemicals listed under the U. S Clean Water Act Hazardous Substance List: • NONE The following chemicals are listed as primary pollutants: • NONE |
| FDA: Food Packaging Status | This product has not been cleared by the FDA for use in food packaging and / or other applications as an indirect food additive. |
| Occupational Safety and Health Act | This product is considered to be hazardous under the OSHA Hazard Communication Standard. Its hazard are: • IMMEDIATE (acute) HEALTH HAZARD • FIRE HAZARD |
| RCRA | This product contains chemicals considered to be hazardous waste under RCRA (40 CFR 261): Ethyl Acetate CAS# 141-78-6, RCRA Code U112 |
| SARA Title III: Section 302 (TPQ) | This product contains no chemicals regulated under Sec. 302 as extremely hazardous Substances. |
| SARA Title III: Section 302 (RQ) | This product contains chemicals regulated under Section 304 as extremely hazardous chemicals for emergency release notification ("CERCLA" List): • Ethyl Acetate, CAS #141-78-6, RQ (Lbs): 5000 |
| SARA Title III: Section 311-312: | This product is considered hazardous under the OSHA Hazard Communication Standard and is regulated under Section 311-312 (40 CFR 370). Its hazards are: Immediate (acute) health hazard Delayed (chronic) health hazard Reactive hazard |
| SARA Title III: Section 313: | This product contains no chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372. |

PRODUCT NAME: Cuccio Colour Veneer- Fuse Date: August 19, 2015

Labeling according to EC directives - 1999/45/EC European Community:





PREP:

- Hazard Symbols: Xi, F
- Risk Phrases: R11, highly flammable, R36: Irritating to eyes, R43: May cause sensitization by skin contact, R66: repeated exposure may cause skin dryness and cracking, R67: Vapors may cause drowsiness and dizziness.
- Safety Phrases: S16: keep away from sources of ignition—no smoking, S26: in case of contact with eyes, rinse immediately, S28A: after contact with skin, wash immediately with plenty of water, S33: take precautionary measures against static discharges, S36/37: Wear suitable protective clothing and gloves.

SECTION 16: ADDITIONAL REGULATORY INFORMATION

EU Classes and Risk / Safety Phrases for Referenced Ingredients (See Section 2):

Hazard Symbol:

F – Flammable substances or preparations

Xi - Irritants

Risk Phrases:

R11 Highly flammable; R36 Irritating to eyes; R36/38 Irritating to eyes and skin

R43 May cause Sensitization by skin contact; R66 Repeated exposure may cause skin dryness or cracking; R67 Vapors may cause drowsiness

and dizziness

Safety Phrases:

S2 Keep out of the reach of children; S16 Keep away from sources of ignition – No smoking; S26 In case of contact with eyes, rinse

immediately with plenty of water and seek medical advice; S28 After contact with skin, wash immediately with plenty of water; S33 Take

precautionary measures against static discharges

Hazard Rating System:

NFPA: Health (2) Flammabilty (3) Reactivity (1)





HMIS: Health (2) Flammability (3) Reactivity (1)

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

PRODUCT NAME: Cuccio Colour Veneer- Fuse Date: August 19, 2015

Preparation Date of SDS: 08/19/2015

DISCLAIMER: This SDS is intended to provide a brief summary of our knowledge and guidance regarding the use of this material. The information contained here has been compiled from sources considered by us to be dependable and is accurate to the best of the Company's knowledge. It is not meant to be an all-inclusive document on worldwide hazard communication regulations.

This information is offered in good faith. Each user of this material needs to evaluate the conditions of use and design and the appropriate protective mechanisms to prevent employee exposure, property damage or release to the environment. Star Nail International assumes no responsibility for injury to the recipient or third persons, or for any damage to any property resulting from misuse of the product.

SECTION 17: OTHER INFORMATION

HAZARDOUS MATERIAL INDENTIFICATION SYSTEM (HMIS) RATING:

HEALTH: 2 3 FLAMMABILITY: REACTIVITY:

PERSONAL PROTECTION EQUIPMENT: Gloves and Safety Glasses

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) HAZARD IDENTIFICATION RATING:

HEALTH: 2 3 FLAMMABILITY: 1 **REACTIVITY:**

ABBREVIATIONS:

| NA NE | Not Applicable Not Established | ND | Not Determined |
|----------------------------|--------------------------------------------------------------|-------------------------|------------------------------------------|
| pm mg gm kg Pa | Part per million Milligram Gram Kilogram Pascals | G L mol u p | Gallon Liter Mole Micro Pico |
| 10 | Lathal Canaantration | ID | Lathal Dasa |

LC Lethal Concentration LD Lethal Dose

TC Toxic Concentration TD Toxic Dose

BOD Biological Oxygen Demand COD Chemical Oxygen Demand

TLm **Threshold Limit**

DOC Dissolved Organic Carbon

Η Hours M Months D Days Υ Years

W Weeks

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

PRODUCT NAME: Cuccio Colour Veneer- Fuse Date: August 19, 2015

ACGIH American Conference of Governmental Industrial Hygenist

CPR Controlled Product's Regulation
DSL Canadian Domestic Substances List

NDSL Canadian Non-Domestic Substance List IARC International Agency for Research for Cancer

NOEL No Observed Effect Level

NOAEL No Observed Adverse Effect Level

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit TLV Threshold Limit Value

END OF SDS

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.