This form is regarded to be in compliance with 29 CFR Part 1910.1200

SECTION 1 : IDENTIFICATION

PRODUCT NAME: CUCCIO PRO POWDER POLISH DIP SYSTEM LAYERING GEL DIP

Product Use: Nail glue

Manufacturer's Name : Star Nail International, Inc. Chemical Family : Address : 29120 Avenue Paine Proprietary Mix Caty, State, Zip : Valencia, CA 91355 CAS# N/A

Preparation Date: 09/28/2016

24 HR. EMERGENCY TELEPHONE: CHEMTEL 1-813-248-0573

SECTION 2: Hazardous Identification

GHS CLASSIFICATIONS

Health:

Eye Irritation, Category 2A Skin Irritation, Category 2 Target Organ Toxicity (Single exposure), Category 3 Skin Sensitization, Category 1

Physical:

Flammable Liquids, Category 4

GHS LABEL ELEMENTS



SIGNAL WORD: WARNING HAZARD STATEMENTS

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H317: May cause an allergic skin reaction.

H335: May cause respiratory irritation.

H227: Combustible liquid.

PRECAUTIONARY STATEMENT(S)

Prevention:

P264: Wash skin and hands thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P271: Use only outdoors or in a well-ventilated area.

SAFETY DATA SHEET

PRODUCT NAME: CUCCIO PRO POWDER POLISH DIP SYSTEM LAYERING GEL DIP Date: 09/28/2016

P210: Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Response:

P370: In case of fire: Use dry chemical, foam or carbon dioxide to extinguish.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eve irritation persists: Get medical advice/attention.

P313: Get medical advice/attention.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P362: Take off contaminated clothing and wash before reuse.

P304+P340: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

P312: Call a POISON CENTER or doctor/physician if you feel unwell.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P403+P235: Store in a well-ventilated place. Keep cool.

P405: Store locked up.

Disposal:

7944L5O1: Dispose of in a manner consistent with federal, state, and local regulations.

SECTION 3: Composition/Information on Ingredients

Chemical Name	Wt.%	CAS
ETHYL-2-CYANOACRYLATE	85 - 100	7085-85-0

SECTION 4: First Aid Measures

EYES: Immediately flush eyes with plenty of water for at least 15 minutes. Get immediate medical attention.

SKIN: Wash with soap and water. Peel or roll skin apart.

INGESTION: Peel or roll skin apart. Adhesive becomes solid in contact with saliva and may adhere to inside of mouth. Saliva will lift adhesive in 1-2 days. Avoid swallowing solid adhesive after detachment. Not a toxic product.

INHALATION: Remove to fresh air. Prolonged or repeated elevated exposure may cause allergic reactions with asthma-like symptoms in sensitive individuals.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Causes serious eye irritation. Will bond eyelids. Will cause excessive tearing.

SKIN: Bonds skin in seconds. May cause skin irritation. May cause sensitization by skin contact. Cyanoacrylates generate heat on polymerization, so very large amounts will burn the skin.

INGESTION: Adhesive becomes solid in contact with saliva and may adhere to inside of mouth. Saliva will lift adhesive in 1-2 days. Not a toxic product.

INHALATION: Prolonged or excessive inhalation may cause respiratory tract irritation.

ACUTE TOXICITY: Avoid exposure to vapor concentration in confined areas.

CHRONIC EFFECTS: Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis).

SECTION 5: Fire Fighting Measures

GENERAL HAZARD: Combustible liquid and vapor. Product polymerized to solid by water.

EXTINGUISHING MEDIA: Use dry chemical extinguisher or flush with large amounts of water.

HAZARDOUS COMBUSTION PRODUCTS: Can burn in fire, releasing irritanting vapors

EXPLOSION HAZARDS: None Known.

FIRE FIGHTING PROCEDURES: Evacuate area and fight fire from a safe distance.

FIRE FIGHTING EQUIPMENT: As in any fire, wear self-contained breathing apparatus pressure-demand, (MSHA/NIOSH

approved or equivalent) and full protective gear.

SENSITIVE TO STATIC DISCHARGE: None Known.

SENSITIVITY TO IMPACT: None Known.

FIRE EXPLOSION: None Known.

HAZARDOUS DECOMPOSITION PRODUCTS: Combustible by-products of carbon monoxide/dioxide.

SECTION 6 : Accidental Release Measures

SMALL SPILL: Polymerize with water. Solid material may be scraped from surface.

LARGE SPILL: Polymerize with water. Increase ventilation to area. Solid material may be scraped from surface.

ENVIRONMENTAL PRECAUTIONS

WATER SPILL: This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

SECTION 7 : Handling and Storage

GENERAL PROCEDURES: Use with adequate ventilation. Avoid contact with eyes, skin and clothing.

HANDLING: Avoid breathing (dust, vapor, mist, gas). Avoid contact with skin, eyes and clothing. Keep container closed when not in use.

STORAGE: Store in a cool place in original container and protect from sunlight. Keep away from sources of ignition.

STORAGE TEMPERATURE: Ideal storage: 41-50F (5-10C)

SECTION 8 : Exposure Controls/ Personal Protection

EXPOSURE GUIDELINES

EXPOSONE GOIDELINES							
OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)							
		EXPOSURE LIMITS					
		OSHA PEL ACGIH TLV SupplierOEL			erOEL		
Chemical Name		ppm	mg/m³	ppm	mg/m³	ppm	mg/m³
ETHYL-2-CYANOACRYLATE	TWA	[1]	[1]	0.2	1.0	0.2 ppm	
OSHA TABLE COMMENTS: 1. NL = Not Listed							

ENGINEERING CONTROLS: Use only in a well ventilated area. Local exhaust ventilation may be necessary to control any air contaminants to within their TLVs during the use of this product.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: For normal conditions, wear safety glasses. Where there is reasonable probability of liquid contact, wear splash-proof goggles.

SKIN: Use Nitrile gloves and aprons to prevent contact. Do not use PVC, Nylon or Cotton materials.

RESPIRATORY: Use only in a well-ventilated area. In case of insufficient ventilation, wear suitable respiratory equipment. Recommended: Full-face NIOSH-approved respirator with organic vapor cartridge.

WORK HYGIENIC PRACTICES: Avoid direct contact and breathing vapor. Use with adequate ventilation. Wash hands with soap and water after use.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

SECTION 9 : Physical and Chemical Properties

PHYSICAL STATE: Liquid

ODOR: Characteristic odor, intensely irritating.

ODOR THRESHOLD: Odor Threshold = 1 ppm

APPEARANCE: Transparent, colorless liquid.

pH: Not Applicable.

PERCENT VOLATILE: Not Available

FLASHPOINT AND METHOD: 80°C (176°F) to 93.4°C (200°F) TAG CC

FLAMMABLE LIMITS: Not Available

AUTOIGNITION TEMPERATURE: 485 °C (905 °F)

VAPOR PRESSURE: < 0.2 mm Hg VAPOR DENSITY: Not Available BOILING POINT: > 149 °C (300 °F) FREEZING POINT: Not Available MELTING POINT: Not Determined

THERMAL DECOMPOSITION: Not Available

SOLUBILITY IN WATER: Insoluble

EVAPORATION RATE: Not Established

DENSITY: Not Available

SPECIFIC GRAVITY: 1.06 g/mL at 25°C

VISCOSITY #1: 25 to 50 Centipoise at 22°C (72°F)

MOLECULAR WEIGHT: Not Available

(VOC): < 20.000 g/L Per SCAQMD Method 316B.

COEFF. OIL/WATER: Partition coefficient (octanol/water): Not applicable.

SECTION 10 : Stability and Reactivity

STABLE: Yes

HAZARDOUS POLYMERIZATION: No

CONDITIONS TO AVOID: Avoid temperatures above 176°F (80°C), moisture and alkalines.

POSSIBILITY OF HAZARDOUS REACTIONS: Possible polymerization reaction in the presence of water, amines, alkalis and alcohols.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Dioxide, Carbon Monoxide and other toxic or irritating compounds may form when heated to decomposition. Oxides of nitrogen and probably hydrogen cyanide are also possible.

INCOMPATIBLE MATERIALS: Polymerized by water, alcohol, amines, alkaline materials.

COMMENTS: REACTIVITY: Rapid exothermic polymerization will occur in the presence of water, amines, alkalis and alcohols.

SECTION 11: Toxicological Information

ACUTE

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)
ETHYL-2-CYANOACRYLATE	> 5000 mg/kg	> 2000 mg/kg

DERMAL LD₅₀: > 2000 mg/kg

Notes: (Estimated)

ORAL LD₅₀: > 5000 mg/kg

Notes: (Estimated)

INHALATION LC50: Vapors may be irritating. Recommended TWA 0.2ppm.

EYE EFFECTS: Bonds skin and eyes in seconds. Eye irritant.

SKIN EFFECTS: Irritating to skin. May cause allergic skin reaction with prolonged contact.

CARCINOGENICITY
IARC: None known
NTP: None known
OSHA: None known

SENSITIZATION: Possible skin sensitizer.

TARGET ORGANS:

<u>Ingredient</u>	Health Effect/ Target Organ	
Ethyl cyanoacrylate	Irritant, Allergen/ Respiratory, Skin	

SECTION 12: Ecological Information

ENVIRONMENTAL DATA:

This material is a water pollutant and should be prevented from contaminating soil or from entering sewage and drainage systems and bodies of water.

SECTION 13: Disposal Considerations

DISPOSAL METHOD: Dispose of following all Local Authority requirements for disposal.

SECTION 14: Transport Information

DOT (DEPARTMENT OF TRANSPORTATION)
PROPER SHIPPING NAME: Not restricted

ROAD AND RAIL (ADR/RID)

PROPER SHIPPING NAME: Not restricted

AIR (ICAO/IATA)

SHIPPING NAME: Not regulated (less than 500 mL). AVIATION REGULATED LIQUID, N.O.S. (ETHYL CYANOACRYLATE),

UN3334, 9.

VESSEL (IMO/IMDG)

SHIPPING NAME: Not restricted

CANADA TRANSPORT OF DANGEROUS GOODS

SHIPPING NAME: Not restricted

.....

SECTION 15: Regulatory Information

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Immediate Health, Delayed Health, Fire, Reactive.

313 REPORTABLE INGREDIENTS: None above reporting de minimus.

302/304 EMERGENCY PLANNING

EMERGENCY PLAN: None above reporting de minimus.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
ETHYL-2-CYANOACRYLATE	7085-85-0

TSCA STATUS: All components are listed on or are exempt from listing on the Toxic Substances Control Act.

CLEAN AIR ACT

40 CFR PART 68—RISK MANAGEMENT FOR CHEMICAL ACCIDENT RELEASE PREVENTION: Not applicable.

CALIFORNIA PROPOSITION 65: No California Proposition 65 ingredients are known to be in this product.

CANADA

WHMIS HAZARD SYMBOL AND CLASSIFICATION





Liquid

Class B3 - Combustible, D2B - Irritant.

WHMIS CLASS: B3 - combustible, D2B - irritant.

DOMESTIC SUBSTANCE LIST (INVENTORY): All components are listed on or are exempt from listing on the Domestic Substances List.

SECTION 16: ADDITIONAL REGULATORY INFORMATION

DISCLAIMER: This SDS is intended to provide a brief summary of our knowledge and guidance regarding the use of this material. The information contained here has been compiled from sources considered by us to be dependable and is accurate to the best of the Company's knowledge. It is not meant to be an allinclusive document on worldwide hazard communication regulations.

This information is offered in good faith. Each user of this material needs to evaluate the conditions of use and design and the appropriate protective mechanisms to prevent employee exposure, property damage or release to the environment. Star Nail International assumes no responsibility for injury to the recipient or third persons, or for any damage to any property resulting from misuse of the product.

END OF SDS