

MATERIAL SAFETY DATA SHEET

SECTION 1: Material Identification

Material Name: NAIL ART PAINT

Date: Feb 03, 2012

Material Description: nail art paint

Manufacturer: Princess Nail Art Inc.

5G,building 4,No.398,South He Nan Road, 200010, Shanghai China

Emergency Phone Numbers: Telephone: +86-21-63340465/63340469

SECTION 2: Composition/Information on Ingredients

CAS#	INCI Name	Percent	TLV	PEL
7732-18-5	AQUA	75%	Not applicable	Not applicabl
9003-01-4	Polyacrylic Acid	24%	Not established	Not established
NA	PIGMENT	1 %	Not established	Not established

SECTION 3: Hazards Identification

* Emergency Overview *

Liquid. Not Combustible. May cause eye, skin or respiratory irritation, dizziness, headache, nausea.

Eves: Irritation Skin: Irritation

Effects of Short-Term Overexposure:

Inhalation: Irritation, headache, dizziness, nausea

Ingestion: Irritation, nausea

Effects of Chronic Overexposure: ND Material Exposure Limits: See Section 2 for information on ingredients.

Routes of Entry: Contact, inhalation, ingestion

Target Organs: Eyes, skin, respiratory system, stomach, nervous system

Cancer Rating: This material does not contain more than 0.1% of any chemical listed by NTP, IARC or OSHA as being carcinogenic.

Additional Information: Not available.

SECTION 4: First Aid Measures

Eyes: Immediately flush eyes with plenty of water. Seek medical attention if irritation persists.

Skin: Remove contaminated clothing. Wash with soap and water. Seek medical attention if necessary.

Inhalation: If exposed to excessive levels, remove to fresh air. Seek medical attention if necessary. Ingestion: Rinse mouth if conscious. Call poison control center. Do not induce

vomiting unless advised to do so by the poison control doctor.

SECTION 5: Fire Fighting Measures

Flash Point: > 212 °F, non flammable Method Used: CC (ASTM D3828)

Flammable Limits (Percentage in air):

UEL: ND

heat.

LEL: ND

Extinguishing Media: Foam, carbon dioxide, dry chemical, water spray **Control Measures:** Use self-contained breathing apparatus and full turn-out gear. Use

water spray to cool containers.

Unusual Hazards: Closed containers may rupture or explode when exposed to extreme

SECTION 6: Accidental Release Measures

Spills: Use personal protective equipment. Ventilate area. Contain spilled material and soak up with inert absorbant. Collect for disposal.

Releases to the air: Not applicable

SECTION 7: Handling and Storage

SECTION 8: Exposure Controls and Personal Protection

Protective equipment:*

Eyes: Safety glasses or chemical goggles **Skin:** Impervious gloves should be worn to prevent prolonged or repeated skin

contact **Respiratory:** A NIOSH/MSHA approved air-purifying respirator if exposure

limits exceeded

Good general ventilation should be sufficient to control airborne levels. Ventilation: Use process enclosures, local exhaust ventilation, or other engineering controls to

Handling: Avoid personal contact. Use with adequate ventilation. Wash after handling. **Storage requirements:** Keep container closed and upright. Do not store above 120 °F.

maintain airborne levels below recommended exposure limits. Additional information: None

*Protective equipment should be determined by conditions of exposure.

SECTION 9: Physical and Chemical Properties

Appearance and Odor: liquid, Slight odor

Specific gravity (water = 1): 1.01-1.05

Boiling point: > 212.0 °F Melting/freezing point: ND

Percent volatile: 70 - 80% /wt

VOC: 4.9 % (0.42 lbs./gal (50 g/l) as supplied, 1.56 lbs/gal (187 g/l) excluding water

Vapor pressure: ND Vapor density (air = 1): ND Evaporation rate (n-Butyl acetate = 1): ND

pH: ND Solubility in water: Miscible

SECTION 10: Stability and Reactivity

Stability: Stable

Conditions to avoid: Not applicable Hazardous polymerization: Not applicable Conditions to avoid: Not applicable

> Page 3 10/2/2012

SECTION 11: Toxicological Information No information available at this time. **SECTION 12: Ecological Information**

No information available on this product.

Hazardous decomposition products: CO, CO₂

SECTION 13: Disposal Procedures

Incompatibility: Strong oxidizers

Unusual hazards: Not applicable

Material and containers should be disposed in accordance with local, state and federal regulations. Empty Container Warning: Empty containers retain residue (liquid and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose

due the non-flammability of this product). Do not attempt to clean since residue is difficult to remove. Empty containers should be completely drained and properly disposed of in an environmentally safe manner and in accordance with governmental regulations.

California Proposition 65: WARNING: This product contains chemical(s) known to

such containers to heat, flame, sparks, or other sources of ignition; THEY MAY EXPLODE AND CAUSE INJURY OR DEATH (however this is extremely unlikely

SECTION 14: Transportation Information

DOT Hazard Classification: Not regulated

the State of California to cause cancer.

SECTION 15: Regulatory Information

SARA Title III Section 302 Extremely Hazardous Substances above de minimis

CERCLA Hazardous Substances above de minimis level: None

SARA Title III Section 313 Toxic Chemicals above de minimis level:

None.

None

level: None

Page 4 10/2/2012

California Proposition 65: WARNING: This product contains chemical(s) known to the State of California to cause birth defects or other reproductive harm.
None.
SECTION 16: Other Information
Abbreviations:
NA - Not applicable ND - Not determined
General Finishes believes that the information contained in this MSDS is correct as of this date. However, because the material may be used under conditions over which General Finishes has no control or in ways we cannot anticipate, we give no warranty, expressed or implied, as to the accuracy of the information. General Finishes assumes no responsibility for any damage to person, property or user of this material or to insure that it is properly and safely used.
End of MSDS
10/2/2012