

# MATERIAL SAFETY DATA SHEET

## **Section 1. Product and Company Identification**

Product Name: Ardell LashTite Adhesive For Individual Lashes - Dark DATE: 4/12/2010

Formula: 30-0060 REV. 03

Item#: 130430

Manufacturer: American International Industries

2220 Gaspar Ave

Los Angeles, CA 90040

Chem-Tel: (800) 255-3924

## Section 2. Composition / Information on Ingredients

### **Hazardous Ingredients:**

Component	CAS#	%	TOXICOLOGICAL DATA
Methoxyisopropyl Acetate	108-65-6	35 - 45%	OSHA PEL: 800 ppm
Diethyl Phthalate	84-66-2	1 - 10%	OSHA TWA: 5 mg/m3
Nitrocellulose	9004-70-0	20 - 35%	Not Established
Alcohol Denat.	64-17-5	20 - 35%	OSHA PEL: 1000 ppm

### Potential Health Effects, Signs and Symptoms of Exposure:

Eye: Liquid and vapor may cause irritation. Splashes may cause temporary pain and blurred vision. Skin: May cause irritation, cracking, flaking and defatting of skin. Avoid contact with damaged skin.

Ingestion: Can cause depression of Central Nervous System, nausea, vomiting, and diarrhea.

Inhalation: May cause irritation to mucous membranes of the upper respiratory tract. Excess exposure

may cause headache, drowsiness, and inability to concentrate.

# Section 4. First Aid Measures

First Aid for Eye: Irrigate with gently flowing water immediately and continuously for up to 15 minutes while

holding eyelids open. Consult medical personnel if irritation persists.

First Aid for Skin: Flush with plenty of water for at least 15 minutes and wash with mild soap. Launder

contaminated clothing before reuse. Consult physician if irritation persists.

First Aid for Inhalation: If ill effects occur, remove to fresh air. If breathing has stopped, perform artificial respiration.

Seek medical attention as needed.

First Aid for Ingestion: If conscious and able to swallow, victim should drink plenty of water to dilute. Call physician or

Poison Control Center immediately.

### Section 5. Fire Fighting Measures



# MATERIAL SAFETY DATA SHEET

Flash Point (°F/°C): <73°F / 22.7°C

Flammable Limit

(vol%):

Not available

Auto-ignition Temp.

(vol%)

None Established

Extinguisher Media: Use water, "alcohol" foam, dry chemical, or carbon dioxide.

Fire Fighting Procedures:

Attempt to contain and/or cool product with water spray. Wear full bunker gear while controlling

fire in confined areas.

Unusual Fire and

Explosion Hazards:

Keep containers cool and away from flames, and sources of ignition. Do not crush or puncture containers. Closed containers exposed to excessive heat may rupture. Vapors may travel across the ground and reach remove ignition sources causing a flashback. Do not allow bulk

product to dry as Nitrocellulose is highly dangerous in dry state.

### Section 6. Accidental Release Measures

Spill or Release Procedures: For small spills or leaks, contain spill with inert material; sweep up, and place in a disposal container. For large spills, dike far ahead of spill for later disposal. Do not release into sewers or water-ways.

# Section 7. Handling and Storage

Handling & Storing: Practice good personal hygiene after handling this product. Protect containers from physical

damage, shield them from direct sunlight, and store in cool, dry area.

## Section 8. Exposure Controls / Personal Protective Equipment

### For Manufacturing Use Only:

Ventilation: Use local Exhaust.

Protective Gloves: Neoprene gloves.

Eye Protection: Include splash guards and side shields.

Respiratory

Use with adequate Ventilation and avoid breathing vapors.

Protection:

Clothing: Coveralls.

Other Protective Eye bath and shower.

### Section 9. Physical and Chemical Properties

### AMERICAN INTERNATIONAL INDUSTRIES



# **MATERIAL SAFETY DATA SHEET**

Appearance: Black, semi-viscous liquid

Odor: Characteristic pH Not applicable

Specific Gravity: 0.99

Ignition:Not applicableMelting Point:Not applicableBoiling Range:>78°C / 172.4°FSolubility in WaterDispersible

Viscosity (RVT): 1,000 - 4,000 Vapor Pressure: Not Available

Not Available

# Section 10. Stability and Reactivity

Stability: Stable

### **Hazardous Decomposition Products:**

Excessive heat may cause carbon monoxide, carbon dioxide, oxides of nitrogen, and unidentified organic compounds to be released.

Vapor Density:

### Incompatibility (Materials to Avoid):

Heat, sparks, flame, strong acids, and contact with strong oxidizing agents.

#### **Hazardous Polymerization:**

Will not occur

# **Section 11. Toxicological Information**

Results of component toxicity test performed:

No data

Human experience:

No data

# Section 12. Ecological Information

**Ecological Information:** 


No data

Chemical Fate Information:

No data

### Section 13. Disposable Considerations

# AMERICAN INTERNATIONAL INDUSTRIES



# **MATERIAL SAFETY DATA SHEET**

Disposal requirements are dependent on hazard classification and will vary by location and the type of disposal selected. It is suggested that all local, state, and federal regulations concerning health and pollution be reviewed to determine approved disposal methods.

# Section 14. Transportation Information

<DOT Information>

Proper Shipping Name: Consumer Commodity

DOT Hazard Class: ORM-D UN ID Number UN 1993

# Section 15. Regulatory Information

Regulatory Information Available Upon Request

### Section 16. Other Information

No additional information available.