

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

CHEMICAL NAME: Methacrylate Monomer

PRODUCT NAME: Ultra Clear Monomer

TRADE NAME/PRODUCT CODE: 0000

PRODUCT USE: Organic Process Chemical

MANUFACTURER: Star Nail International
ADDRESS: 29120 Avenue Paine
Valencia CA 91355

24 HR. EMERGENCY TELEPHONE: CHEMTEL 1-800-255-3924

PREPARATION/UPDATE DATE: 08/11/2015
PRINT DATE: 9/2/15
MSDS ID: M30-01

SECTION 2 - COMPOSITION/INFORMATION ON INGREDIENTS

ITEM	CHEMICAL NAME	CAS NUMBER:	WT/WT %
01	Ethyl Methacrylate Monomer	97-63-2	60.0-100.0
02	Ethylene Glycol Dimethacrylate	97-90-5	0.0-20.0
03	Isopropyl Alcohol	67-63-0	0.0-20.0
04	N,N-Dimethyl-p-Toluidine	99-97-8	0.0-2.0

ITEM	ACGIH		OSHA		Company Recommendation	SKIN
	TLV-TWA	TLV-STEL	PEL TWA	PEL CEILING		
01	NE	NE	NE	NE	100 ppm	NE
02	NE	NE	NE	NE	NE	NE
03	200 ppm	400 ppm	400 ppm	NE	400 ppm	NE
04	NE	NE	NE	NE	NE	NE

Note this material contains an inhibitor (HQ, MEHQ, etc) at <1%. The type and amount meet product specifications.
Contact manufacturer for exact concentration and details on inhibitor level maintenance.

See Section 16 for Abbreviations.

SECTION 3 - HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:**WARNING:**

For Monomer:



Physical Hazards:	Unstable/Reactive upon depletion of inhibitor. Check inhibitor levels periodically.
Acute Hazards:	<p>Ingestion: Causes irritation, a burning sensation of the mouth, throat and respiratory tract and abdominal pain. Symptoms of over exposure to Isopropyl Alcohol may include nausea and vomiting, headache, facial flushing, dizziness, lowered blood pressure, mental depression, hallucinations and distorted perceptions, difficulty breathing, respiratory depression, stupor, unconsciousness and coma.</p> <p>Eyes: Eye contact may cause irritation with discomfort, tearing, or blurring of vision and possible corneal burns.</p> <p>Inhalation: High concentrations irritant to the respiratory tract and may cause dizziness, headache and anesthetic effects.</p> <p>Skin: May cause skin irritation and can cause skin sensitization. Extensive/prolonged or repeated exposure to this material may result in a more severe skin response. Symptoms may be delayed.</p>
Chronic Hazards:	<p>Ingestion: Isopropyl Alcohol exposure may lead to kidney insufficiency including oliguria, anuria, nitrogen retention, and edema may occur.</p>
Aggravating Pre-existing Conditions:	Dermatitis, respiratory or kidney disorders.

Note to Physicians:

This product contains N,N-Dimethyl-p-Toluidine at a low concentration (Refer to Section 2). While complications from this component are not expected, absorption leads to formation of methemoglobin, which in sufficient concentration causes cyanosis. Symptoms may include headaches, weakness and dizziness, and can be recognized by the blue color of the lips, fingernails, nose and earlobes. Reversion of methemoglobin to hemoglobin occurs spontaneously after termination of exposure, moderate degree of cyanosis needs to be treated only by supportive measures such as bed rest and oxygen inhalation. Thorough cleansing of the entire contaminated area of the body is of utmost importance. If cyanosis is severe, intravenous injection of methylene blue, 1-2 mg/kg body weight over a 5 minute period as a 1 % solution may be of value. If elevated methemoglobin persists after an hour, the treatment may be repeated, but the total dose should not exceed 7 mg/kg body weight. Cyanocobalmin (Vitamin B-12), 1 mg intramuscularly is reported to speed recovery. Intravenous fluids and blood transfusions may be indicated in very severe exposures.

CARCINOGENICITY: Ethylene Glycol Dimethacrylate may contain trace amounts of substances known to the state of California to cause cancer and/or reproductive toxicity. None of the other components of this material are listed by IARC, NTP, OSHA, or ACGIH as carcinogens.

PRIMARY ROUTES OF ENTRY: Inhalation, Skin or Eyes.

SECTION 4 - FIRST AID MEASURES

EMERGENCY AND FIRST AID PROCEDURES:

- EYES:** If product gets in the eyes, flush with copious amounts of lukewarm water for at least 15 minutes. If irritation occurs, contact a physician.
- INGESTION:** If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give anything by mouth to an unconscious person. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed. Get medical attention immediately.
- INHALATION:** Remove to fresh air. Seek immediate medical attention.
- SKIN:** If irritation occurs and product is on the skin, rinse thoroughly with lukewarm water, followed by a thorough washing of the effected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately.
- CLOTHING:** Remove contaminated clothing, wash thoroughly before reuse.
- TREATMENT:** Treat symptoms conventionally, after thorough decontamination.

SECTION 5 - FIRE FIGHTING MEASURES

FLASH POINT: 19 °C, 67°F

FLAMMABLE LIMIT, AIR VOL% LOWER: 1.8
UPPER: Saturation concentration.

AUTOIGNITION TEMPERATURE: 411 °C, 771 °F

EXTINGUISHER METHOD: Alcohol resistant foam, carbon dioxide, dry chemical, water spray.

FIRE AND EXPLOSION HAZARDS: High temperatures, inhibitor depletion, accidental impurities, or exposure to radiation or oxidizers may cause spontaneous polymerizing reaction generating heat/pressure. Closed containers may rupture or explode during a runaway polymerization. Use a water spray or fog to reduce or direct vapors. Water may not be effective in actually extinguishing a fire involving this product. Alcohol poses an explosion threat indoors, outdoors and in sewers.

SPECIAL FIRE FIGHTING PROCEDURES: This product is a flammable liquid. When involved in a fire, this product may ignite readily and decompose to produce carbon oxides. Vapors of this product are heavier than air and may travel to a source of ignition and flash back to a leaking or open container. Do not enter fire area without proper protection. Fight fire from a safe location. Heat/impurities may cause pressure to build and/or rupture closed containers, spreading fire, increasing risk of burns/injuries. Structural firefighters must wear SCBAs and full protective equipment.

SENSITIVE TO MECHANICAL IMPACT: No.

SENSITIVE TO STATIC DISCHARGE: Yes.



SECTION 6 - ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE:

Before cleaning any spill or leak, individuals involved must wear appropriate Personal Protective Equipment (e.g., goggles, gloves). Deny entry to all unprotected individuals. Dike and contain spill with inert material (e.g. sand or earth). Use ONLY non-sparking tools for recovery and cleanup. Maximize ventilation (open doors and windows) and secure all sources of ignition. Place into appropriate closed container(s) for disposal in accordance with local, state and federal regulations. Wash all affected areas with plenty of warm water and soap. Remove any contaminated clothing and wash thoroughly before reuse. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water.

SECTION 7- HANDLING AND STORAGE

- PRECAUTIONS FOR HANDLING:** Use local explosion-proof ventilation with a minimum capture velocity of 100 ft/min (30 m/min) at point of material release. Refer to Industrial Ventilation: A Manual of Recommended Practice published by the American Conference of Governmental Hygienist. Observe precautions found on label.
- PRECAUTIONS FOR STORAGE:** Store containers in a cool, dry location, away from direct sunlight, heat, sparks, flame, other light sources, or sources of intense heat. Keep container closed after each use. Ground and bond all containers when transferring. **Check inhibitor levels periodically**, add to the bulk material if needed. Maintain at a minimum, the original 2-inch headspace in the product container. Do not blanket or mix with oxygen-free gas as it renders the inhibitor ineffective.
- INDUSTRIAL HYGIENE PRACTICES:** Avoid contact with skin, eyes, clothing, and prolonged contact with the product. Use good personal hygiene and housekeeping. After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product.

SECTION 8 - EXPOSURE CONTROL/PERSONAL PROTECTION

- VENTILATION:** Refer to Section 7 regarding the ventilation requirements for working with this product. Use explosion-proof local exhaust at processing equipment, including buffers, sanders, grinders and polishers. High temperature processing equipment should be well ventilated.
- RESPIRATORY PROTECTION:** A respirator should be worn whenever workplace conditions warrant a respirator's use. None required if airborne concentrations are maintained below the exposure limit listed in Section 2. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134 or other appropriate governing standard.
- EYE PROTECTION:** Depending on the use of this product, splash or safety glasses may be worn. If necessary, refer to U.S. OSHA 29 CFR §1910.133, or other appropriate governing standard. Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes.
- PROTECTIVE GLOVES:** If anticipated that prolonged & repeated skin contact will occur during use of this product, wear chemical resistant gloves for routine industrial use. If necessary, refer to U.S. OSHA 29 CFR §1910.138, or other appropriate governing standards.
- OTHER PROTECTIVE EQUIPMENT:** No special body protection is required under typical circumstances of use and handling. If necessary, refer to appropriate governing standards. An eyewash station and a safety shower are recommended.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE: Clear, colorless liquid.
ODOR: Acrid, ester-like.
pH: ND
ODOR THRESHOLD: ND
BOILING POINT: NE
FREEZING POINT: NE
VISCOSITY: NE
SPECIFIC GRAVITY (H₂O=1): NE
VAPOR PRESSURE: NE
PERCENT VOLATILE W/W%: NE
VAPOR DENSITY (AIR=1): NE
EVAPORATION RATE (BuAc =1): NE
SOLUBILITY IN WATER: NE
COEFFICIENT OF WATER/OIL DISTRIBUTION: NE

SECTION 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: Temperatures above 21°C, 70°F, localized heat sources (example drum or band heaters) oxidizing conditions, freezing conditions, direct sunlight, ultraviolet radiation, inert gas blanketing.

INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers, strong reducers, free radical initiators, inert gases, oxygen scavengers. Material has strong solvent properties and can soften paint and rubber.

HAZARDOUS DECOMPOSITION PRODUCTS: Oxides of Carbon when burned.

HAZARDOUS POLYMERIZATION: MAY OCCUR: X WILL NOT OCCUR:

STABILITY: UNSTABLE: X STABLE:

SECTION 11- TOXICOLOGICAL PROPERTIES

TARGET ORGANS:
 For Monomers: None Listed.
 For Alcohol: Nervous System and kidneys.
 For N,N-Dimethyl-p-Toluidine: Liver, Central Nervous System, Blood and Skin.

SENSITIVITY DATA:
 For Alcohol:
 Eye Rabbit: 100 mg caused severe irritation.
 Skin Rabbit: 500 mg caused mild irritation.

REPRODUCTIVE:
 For Ethyl Methacrylate Monomer: No information available.
 For Alcohol:
 Inhalation Rat TC_{Lo}: 3500 ppm/7H, 1-19D Preg.

SECTION 11- TOXICOLOGICAL PROPERTIES

TOXICITY DATA:

This product has NOT been tested on animals to obtain toxicology data. There is toxicology data for the components of the product, which is found in scientific literature. Some of this data is presented below.

For Ethyl Methacrylate Monomer:

Dermal Rabbit	LD ₅₀ :	>10,000 mg/kg.
Inhalation Rat	LC ₅₀ :	8300 ppm/4H.
Intraperitoneal Mouse	LD ₅₀ :	1369 mg/kg.
Intraperitoneal Rat	LD ₅₀ :	1223 mg/kg.
Oral Rat	LD ₅₀ :	13468 mg/kg.

For Alcohol:

Inhalation Mouse	LC _{Lo} :	12800 ppm/3H.
Inhalation Rat	LC _{Lo} :	16000 ppm/8H.
Intraperitoneal Guinea Pig	LD ₅₀ :	2560 mg/kg.
Intraperitoneal Rabbit	LD ₅₀ :	667 mg/kg.
Intravenous Cat	LD _{Lo} :	1963 mg/kg.
Intravenous Dog	LD _{Lo} :	1024 mg/kg.
Intravenous Rat	LD ₅₀ :	1088 mg/kg.
Oral Human	TD _{Lo} :	223 mg/kg.
Oral Human	LD _{Lo} :	3570 mg/kg.
Subcutaneous Mouse	LD _{Lo} :	6000 mg/kg.
Skin Rabbit	LD ₅₀ :	12800 mg/kg.

For N,N-Dimethyl-p-Toluidine:

Inhalation Rat	LC ₅₀ :	254 ppm/4H.
Acute Dermal Rat	LD ₅₀ :	>2000 mg/kg.
Ingestion Rat	LD ₅₀ :	1650 mg/kg.

SECTION 12 - ECOLOGICAL INFORMATION

AQUATIC TOXICITY:

There is no specific data available for this product; however, very large releases of this product may be harmful or fatal to overexposed aquatic life. There is ecological data for the components of the product, which is found in scientific literature. Some of this data is presented below.

For Ethyl Methacrylate Monomer:

Daphnia Magna	EC ₅₀ :	> 66 mg/L/48H.
Rainbow Trout	LC ₅₀ :	100 mg/l/96H.
Algae	EC ₅₀ :	>0.70 mg/L/72H.

ENVIRONMENTAL FATE:

For Ethyl Methacrylate Monomer:

Biodegradation: Inherently biodegradable 79% in 28 days.

SECTION 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: When discarded it is a hazardous waste by the EPA under RCRA with the reportable quantity (RQ) of 1000 pounds (40 CFR Part 302) for the ethyl methacrylate monomer. After addition of excess inhibitor, dispose waste material in accordance with Federal, State, and Local regulations.

DISPOSAL OF EMPTY CONTAINERS: Reuse of empty drums or containers is not recommended. Employees should be advised of the potential hazards, due to residual flammable material, associated with empty containers. Dispose of all empty containers properly, in accordance with Federal, State and Local regulations.

SECTION 14 - TRANSPORTATION

DOT/UN SHIPPING NAME: FLAMMABLE LIQUID, NOS
(Ethyl Methacrylate, Stabilized and Isopropyl Alcohol)

DOT/UN CLASS: 3

NA/UN NUMBER: UN 1993

PACKING GROUP: II

LABEL: Flammable Liquid

IMDG CLASS: 3

EmS: 3-07

MFAG: 330

CERCLA RQ: For Ethyl Methacrylate Monomer: 1000 lb.

SECTION 15 - REGULATORY INFORMATION

SARA Reporting Requirements: Yes

SARA Threshold Planning Quantity: There are specific Threshold Planning Quantities for the components of this product.

TSCA Inventory Status: The components of this product are listed on the TSCA Inventory.

CERCLA Reportable Quantity (RQ): Yes

Other Federal Requirements: This product complies with the appropriate sections of the Food and Drug Administration's 21 CFR.

Other Canadian Regulations: This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDL. None of the components of this product are listed on the Priorities Substances List.

State Regulatory Information: This product may contain components that are covered under specific state criteria.

California Prop 65: State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):
WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin: 99-97-8 Dimethyltolylamine 0.1 to 1.0 % Carcinogen



RISK STATEMENTS: R11 – Highly Flammable
R36/37/38 – Irritating to eyes, respiratory system and skin.
R43 – May cause sensitization by skin contact

SAFETY STATEMENTS: S3 – Keep in a cool place.
S7 – Keep container tightly closed.
S9 – Keep container in a well-ventilated place.

S16 – Keep away from sources of ignition – No Smoking.
 S20 – When using do not eat or drink.
 S 29 – Do not empty into drains.
 S33 – Take precautionary measures against static discharges.
 S37/39 – Wear suitable gloves and eye/face protection.

SECTION 16 - OTHER INFORMATION

HAZARDOUS MATERIAL IDENTIFICATION SYSTEM (HMIS) RATING:

HEALTH:	2
FLAMMABILITY:	3
REACTIVITY:	2
PERSONAL PROTECTIVE EQUIPMENT:	Gloves and Safety Glasses or Chemical Splash Goggles.



NATIONAL FIRE PROTECTION ASSOCIATION (NFPA) HAZARD IDENTIFICATION RATING:

HEALTH:	2
FLAMMABILITY:	3
REACTIVITY:	2

ABBREVIATIONS:

NA	Not Applicable	ND	Not Determined
NE	Not Established		
ppm	parts per million	G	Gallon
mg	Milligram	L	Liter
gm	Gram	mol	Mole
kg	Kilogram	μ	Micro
mm	Millimeter	p	Pico
Pa	Pascals	c	cento
LC	Lethal Concentration	LD	Lethal Dose
TC	Toxic Concentration	TD	Toxic Dose
BOD	Biological Oxygen Demand	COD	Chemical Oxygen Demand
Lo	Lowest	ThOD	Theoretical Oxygen Demand
TLm	Threshold Limit	IC	Inhibitory Concentration
DOC	Dissolved Organic Carbon		
H	Hours	M	Months
D	Days	Y	Years
W	Weeks		

ACGIH American Conference of Governmental Industrial Hygienist
 CPR Controlled Product's Regulation
 DSL Canadian Domestic Substances List
 NDSL Canadian Non-domestic Substance List
 IARC International Agency for Research for Cancer
 NOEL No Observed Effect Level
 NOAEL No Observed Adverse Effect Level
 OSHA Occupational Safety and Health Administration
 PEL Permissible Exposure Limit
 TLV Threshold Limit Value

SECTION 16 - OTHER INFORMATION CONTINUED

THIS SAFETY DATA SHEET IS PREPARED IN COMPLIANCE WITH FEDERAL REGULATIONS (29 CFR 1910.1200), CANADIAN WHMIS REGULATIONS, ANY APPLICABLE STATE AND LOCAL REGULATIONS SHOULD BE CONSULTED. THE ABOVE INFORMATION MAY BE BASED IN PART ON INFORMATION PROVIDED BY COMPONENT SUPPLIERS AND IS BELIEVED TO BE CORRECT AS OF THE DATE HEREOF. HOWEVER, NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY USE, OR ANY OTHER WARRANTY IS EXPRESSED OR IS TO BE IMPLIED REGARDING THE ACCURACY OF THESE DATA, THE RESULTS TO BE OBTAINED FROM THE USE OF THE MATERIAL, OR THE HAZARDS CONNECTED WITH SUCH USE. SINCE THE INFORMATION CONTAINED HEREIN MAY BE APPLIED UNDER CONDITIONS BEYOND OUR CONTROL AND WITH WHICH WE MAY BE UNFAMILIAR, AND SINCE DATA MADE AVAILABLE SUBSEQUENT TO THE DATE HEREOF MAY SUGGEST MODIFICATION OF THE INFORMATION, WE ASSUME NO RESPONSIBILITY FOR THE RESULT OF ITS USE. THIS INFORMATION AND MATERIAL IS FURNISHED ON THE CONDITION THAT THE PERSON RECEIVING IT SHALL MAKE HIS/HER OWN DETERMINATION AS TO THE SUITABILITY OF THE MATERIAL FOR HIS/HER PARTICULAR PURPOSE AND ON THE CONDITION THAT HE/SHE ASSUME THE RISK OF HIS/HER USE THEREOF.

Preparation Date of SDS: 08/11/2015

END OF SDS