

Star Nail International, Inc. SAFETY DATA SHEET

PRODUCT NAME: Cuccio Colour Veneer- 2 am in Hollywood Date: August 18, 2015

This form is regarded to be in compliance with 29 CFR Part 1910.1200

SECTION 1 : IDENTIFICATION

PRODUCT NAME: Cuccio Colour Veneer- 2 am in Hollywood

Product Use: Gel Polish

Manufacturer's Name : Star Nail International, Inc. Chemical Family :
Address : 29120 Avenue Paine Proprietary Mix
City, State, Zip : Valencia, CA 91355 CAS# N/A

Preparation Date: August 18, 2015

24 HR. EMERGENCY TELEPHONE: CHEMTEL 1-813-248-0573

SECTION 2: Hazards Identification

OSHA/HCS status : This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).

Classification of the substance or mixture : FLAMMABLE LIQUIDS - Category 3
SKIN CORROSION/IRRITATION - Category 2
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2A
SKIN SENSITIZATION - Category 1A
CARCINOGENICITY - Category 1A
TOXIC TO REPRODUCTION [Fertility] - Category 2
Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 100%

GHS label elements

Hazard pictograms : [Flammable liquid icon] [Health hazard icon] [Exclamation mark icon]

Signal word : Danger

Hazard statements : Flammable liquid and vapor.
Causes serious eye irritation.
Causes skin irritation.
May cause an allergic skin reaction.
May cause cancer.
Suspected of damaging fertility.

Precautionary statements

Prevention : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wear protective gloves. Wear eye or face protection. Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Use explosion-proof electrical, ventilating, lighting and all material-handling equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Keep container tightly closed. Avoid breathing vapor. Do not eat, drink or smoke when using this product. Wash hands thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace.

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

Star Nail International, Inc. SAFETY DATA SHEET
 PRODUCT NAME: Cuccio Colour Veneer- 2 am in Hollywood Date: August 18, 2015

- Response** : IF exposed or concerned: Get medical attention. IF SWALLOWED: Immediately call a POISON CENTER or physician. Rinse mouth. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.
- Storage** : Store locked up. Store in a well-ventilated place. Keep cool.
- Disposal** : Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Hazards not otherwise classified** : None known.

SECTION 3: Composition/Information on Ingredients

- Substance/mixture** : Mixture
- Other means of identification** : Not available.

CAS number/other identifiers

- CAS number** : Not applicable.

| Ingredient name | CAS number | EC number | INCI Name | % |
|--------------------------------|------------|-----------|--|---------|
| Polyurethane acrylate oligomer | Exempt | - | Di-HEMA trimethylhexyl dicarbamate* | 50 - 75 |
| HEMA | 868-77-9 | 212-782-2 | HEMA | 10 - 25 |
| TPO | 75980-60-8 | 278-355-8 | Trimethylbenzoyl diphenylphosphine oxide | 1 - 5 |
| BUTYL ACETATE | 123-86-4 | 204-658-1 | BUTYL ACETATE | 1 - 5 |
| ETHYL ACETATE | 141-78-6 | 205-500-4 | ETHYL ACETATE | 1 - 5 |

May contain one or more of the following components in quantities considered hazardous:

| Ingredient name | CAS number | EC number | INCI Name | % |
|------------------|------------|-----------|---------------------------|------|
| Titanium dioxide | 13463-67-7 | 236-675-5 | Titanium dioxide/CI 77891 | 0-10 |
| D & C yellow #10 | 8004-92-0 | - | Yellow 10/CI 47005 | 0-5 |
| D & C black #2 | 1333-86-4 | 215-609-9 | Black 2/CI 77266 | 0-1 |

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

SECTION 4 : First Aid Measures

Description of necessary first aid measures

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of
- Skin contact** : Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

Most important symptoms/effects, acute and delayed

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : Irritating to mouth, throat and stomach.

Over-exposure signs/symptoms

- Eye contact** : Adverse symptoms may include the following:
pain or irritation
watering
redness
- Inhalation** : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Skin contact** : Adverse symptoms may include the following:
irritation
redness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Indication of immediate medical attention and special treatment needed, if necessary

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

ration
le
of the

SECTION 5: Fire Fighting Measures

Extinguishing media

Suitable extinguishing media : Use dry chemical, CO₂, water spray (fog) or foam.

Unsuitable extinguishing media : Do not use water jet.

Specific hazards arising from the chemical

: Flammable liquid and vapor. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

Hazardous thermal decomposition products

: Decomposition products may include the following materials:
carbon dioxide
carbon monoxide
nitrogen oxides
sulfur oxides
phosphorus oxides
halogenated compounds
metal oxide/oxides

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Do not breathe vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods and materials for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Use spark-proof tools and explosion-proof equipment. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

SECTION 6 : Accidental Release Measures

SECTION 7 : Handling and Storage

Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use explosion-proof electrical (ventilating, lighting and material handling) equipment. Use only non-sparking tools. Take precautionary measures against electrostatic discharges. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

Conditions for safe storage, including any incompatibilities

- : Shield UV light sources. Store between the following temperatures: 0 to 38°C (32 to 100.4°F). Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

 SECTION 8 : Exposure Controls/ Personal Protection

Control parameters

Occupational exposure limits

| Ingredient name | Exposure limits |
|------------------|---|
| titanium dioxide | ACGIH TLV (United States, 6/2013). TWA: 10 mg/m ³ 8 hours. |
| | OSHA PEL 1989 (United States, 3/1989). TWA: 10 mg/m ³ 8 hours. Form: Total dust |
| | OSHA PEL (United States, 2/2013). TWA: 15 mg/m ³ 8 hours. Form: Total dust |
| Butyl acetate | OSHA PEL 1989 (United States, 3/1989). TWA: 150 ppm 8 hours. |
| | TWA: 710 mg/m ³ 8 hours. |
| | STEL: 200 ppm 15 minutes. |
| | STEL: 950 mg/m ³ 15 minutes. |
| | NIOSH REL (United States, 10/2013). TWA: 150 ppm 10 hours. |
| | TWA: 710 mg/m ³ 10 hours. |
| | STEL: 200 ppm 15 minutes. |
| | STEL: 950 mg/m ³ 15 minutes. |
| | ACGIH TLV (United States, 6/2013). TWA: 150 ppm 8 hours. |
| | STEL: 200 ppm 15 minutes. |
| | OSHA PEL (United States, 2/2013). TWA: 150 ppm 8 hours. |
| | TWA: 710 mg/m ³ 8 hours. |
| Ethyl acetate | ACGIH TLV (United States, 6/2013). TWA: 400 ppm 8 hours. |
| | TWA: 1440 mg/m ³ 8 hours. |
| | OSHA PEL 1989 (United States, 3/1989). TWA: 400 ppm 8 hours. |
| | TWA: 1400 mg/m ³ 8 hours. |
| | NIOSH REL (United States, 10/2013). TWA: 400 ppm 10 hours. |
| | TWA: 1400 mg/m ³ 10 hours. |
| | OSHA PEL (United States, 2/2013). TWA: 400 ppm 8 hours. |
| | TWA: 1400 mg/m ³ 8 hours. |
| | OSHA PEL 1989 (United States, 3/1989). TWA: 3.5 mg/m ³ 8 hours. |
| | NIOSH REL (United States, 10/2013). TWA: 3.5 mg/m ³ 10 hours. |
| | TWA: 0.1 mg of PAHs/cm ³ 10 hours. |
| | ACGIH TLV (United States, 6/2013). TWA: 3 mg/m ³ 8 hours. Form: Inhalable fraction |
| | OSHA PEL (United States, 2/2013). TWA: 3.5 mg/m ³ 8 hours. |
| | |
| D & C black #2 | |

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

| | |
|---|--|
| Appropriate engineering controls | : Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment. |
| Environmental exposure controls | : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. |
| Individual protection measures | |
| Hygiene measures | : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location. |
| Eye/face protection | : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles. |
| Skin protection | |
| Hand protection | : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. |
| Body protection | : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. When there is a risk of ignition from static electricity, wear anti-static protective clothing. For the greatest protection from static discharges, clothing should include anti-static overalls, boots and gloves. |
| Other skin protection | : Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. |
| Respiratory protection | : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. |

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

Appearance

| | |
|---|--|
| Physical state | : Liquid. [Gel] |
| Color | : Various |
| Odor | : Characteristic. Acrylate odor |
| pH | : Not available. |
| Melting point | : Not available. |
| Boiling point | : Not available. |
| Flash point | : Closed cup: 49°C (120.2°F) |
| Lower and upper explosive (flammable) limits | : Not available. |
| Vapor pressure | : <0.0013 kPa (<0.01 mm Hg) [room temperature] |
| Vapor density | : Not available. |
| Relative density | : 1.1 to 1.14 |
| Solubility | : Insoluble in the following materials: cold water and hot water. |
| Solubility in water | : Not available. |
| Partition coefficient: n-octanol/water | : Not available. |
| Auto-ignition temperature | : Not available. |
| Viscosity | : Dynamic (room temperature): 1500 to 6000 mPa-s (1500 to 6000 cP) |

SECTION 9 : Physical and Chemical Properties

SECTION 10 : Stability and Reactivity

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

PRODUCT NAME: Cuccio Colour Veneer- 2 am in Hollywood Date: August 18, 2015

- Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- Chemical stability** : The product is stable.
- Possibility of hazardous reactions** : Hazardous polymerization may occur under certain conditions of storage or use. These could cause the product to polymerize exothermically. Unintentional contact with them should be avoided.
- Conditions to avoid** : Avoid all possible sources of ignition (spark or flame). Do not pressurize, cut, weld, braze, solder, drill, grind or expose containers to heat or sources of ignition.
- Incompatible materials** : Reactive or incompatible with the following materials:
oxidizing materials
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological Information

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

Star Nail International, Inc. SAFETY DATA SHEET
 PRODUCT NAME: Cuccio Colour Veneer- 2 am in Hollywood Date: August 18, 2015

Information on toxicological effects

Acute toxicity

| Product/ingredient name | Result | Species | Dose | Exposure |
|-----------------------------|----------------------|---------|--------------|----------|
| 2-hydroxyethyl methacrylate | LD50 Oral | Rat | 5050 mg/kg | - |
| Butyl acetate | LC50 Inhalation Gas. | Rat | 390 ppm | 4 hours |
| | LD50 Dermal | Rabbit | >17600 mg/kg | - |
| | LD50 Oral | Rat | 10768 mg/kg | - |
| Ethyl acetate | LD50 Oral | Rat | 5620 mg/kg | - |
| D & C yellow #10 | LD50 Oral | Rat | 2 g/kg | - |
| D & C black #2 | LD50 Oral | Rat | >15400 mg/kg | - |

Irritation/Corrosion

| Product/ingredient name | Result | Species | Score | Exposure | Observation |
|-------------------------|--------------------------|---------|-------|--------------------------------------|-------------|
| titanium dioxide | Skin - Mild irritant | Human | - | 72 hours 300 Micrograms Intermittent | - |
| Butyl acetate | Eyes - Moderate irritant | Rabbit | - | 100 milligrams | - |
| | Skin - Moderate irritant | Rabbit | - | 24 hours 500 milligrams | - |

Classification

| Product/ingredient name | OSHA | IARC | NTP |
|-------------------------|------|------|-----|
| titanium dioxide | - | 2B | - |
| D & C black #2 | - | 1 | - |

Specific target organ toxicity (single exposure)

| Name | Category | Route of exposure | Target organs |
|---------------|------------|-------------------|------------------|
| Butyl acetate | Category 3 | Not applicable. | Narcotic effects |
| Ethyl acetate | Category 3 | Not applicable. | Narcotic effects |

Information on the likely routes of exposure : Not available.

Potential acute health effects

- Eye contact** : Causes serious eye irritation.
- Inhalation** : Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
- Skin contact** : Causes skin irritation. May cause an allergic skin reaction.
- Ingestion** : Irritating to mouth, throat and stomach.

Symptoms related to the physical, chemical and toxicological characteristics

- Eye contact** : Adverse symptoms may include the following:
 pain or irritation
 watering
 redness
- Inhalation** : Adverse symptoms may include the following:
 reduced fetal weight
 increase in fetal deaths
 skeletal malformations

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

Star Nail International, Inc. SAFETY DATA SHEET
PRODUCT NAME: Cuccio Colour Veneer- 2 am in Hollywood Date: August 18, 2015

- Skin contact** : Adverse symptoms may include the following:
irritation
redness
reduced fetal weight
increase in fetal deaths
skeletal malformations
- Ingestion** : Adverse symptoms may include the following:
reduced fetal weight
increase in fetal deaths
skeletal malformations

Delayed and immediate effects and also chronic effects from short and long term exposure

Short term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Long term exposure

- Potential immediate effects** : Not available.
- Potential delayed effects** : Not available.

Potential chronic health effects

Not available.

- General** : Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.
- Carcinogenicity** : May cause cancer. Risk of cancer depends on duration and level of exposure.
- Mutagenicity** : No known significant effects or critical hazards.
- Teratogenicity** : No known significant effects or critical hazards.
- Developmental effects** : No known significant effects or critical hazards.
- Fertility effects** : Suspected of damaging fertility.

Numerical measures of toxicity

Acute toxicity estimates

| Route | ATE value |
|--------------|------------------|
| Oral | 51273.3 mg/kg |

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

SECTION 12: Ecological Information

| | | | |
|---------------|--|--|--------------------------------|
| Butyl acetate | Acute LC50 1000000 µg/l Marine water Chronic NOEC 0.984 mg/l Fresh water | Fish - Fundulus heteroclitus Algae - Pseudokirchneriella subcapitata - Exponential growth phase | 96 hours 72 hours |
| | Acute LC50 32000 µg/l Marine water | Crustaceans - Artemia salina - Nauplii | 48 hours |
| Ethyl acetate | Acute LC50 18000 µg/l Fresh water | Fish - Pimephales promelas | 96 hours |
| | Acute EC50 2500000 µg/l Fresh water | Algae - Selenastrum sp. | 96 hours |
| | Acute LC50 750000 µg/l Fresh water | Crustaceans - Gammarus pulex | 48 hours |
| | Acute LC50 154000 µg/l Fresh water | Daphnia - Daphnia cucullata | 48 hours |
| | Acute LC50 212500 µg/l Fresh water Chronic NOEC 2400 µg/l Fresh water Chronic NOEC 75.6 mg/l Fresh water | Fish - Heteropneustes fossilis Daphnia - Daphnia magna Fish - Pimephales promelas - Embryo | 96 hours 21 days 32 days |

Bioaccumulative potential

| Product/ingredient name | LogP _{ow} | BCF | Potential |
|-----------------------------|--------------------|----------|-----------|
| 2-hydroxyethyl methacrylate | 0.42 | - | low |
| titanium dioxide | - | 352 | low |
| TPO | - | 53 to 72 | low |
| Butyl acetate | 2.3 | - | low |
| Ethyl acetate | 0.68 | 30 | low |

Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Other adverse effects : No known significant effects or critical hazards.

Toxicity

| Product/ingredient name | Result | Species | Exposure |
|-----------------------------|------------------------------------|--|----------|
| 2-hydroxyethyl methacrylate | Acute LC50 227000 µg/l Fresh water | Fish - Pimephales promelas - Juvenile (Fledgling, Hatchling, Weanling) | 96 hours |
| titanium dioxide | Acute EC50 5.83 mg/l Fresh water | Algae - Pseudokirchneriella subcapitata - Exponential growth phase | 72 hours |
| | Acute LC50 3 mg/l Fresh water | Crustaceans - Ceriodaphnia dubia - Neonate | 48 hours |
| | Acute LC50 5.5 ppm Fresh water | Daphnia - Daphnia magna - Juvenile (Fledgling, Hatchling, Weanling) | 48 hours |

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

Disposal methods

: The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Vapor from product residues may create a highly flammable or explosive atmosphere inside the container. Do not cut, weld or grind used containers unless they have been cleaned thoroughly internally. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

United States - RCRA Toxic hazardous waste "U" List










| Ingredient | CAS # | Status | Reference number |
|--|--------------|---------------|-------------------------|
| Ethyl acetate (I); Acetic acid ethyl ester (I) | 141-78-6 | Listed | U112 |

SECTION 13: Disposal Considerations

SECTION 14: Transport Information

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

PRODUCT NAME: Cuccio Colour Veneer- 2 am in Hollywood Date: August 18, 2015

| | DOT Classification | TDG Classification | Mexico Classification | ADR/RID | IMDG | IATA |
|----------------------------|--|--|---|---|---|--|
| UN number | 1993 | 1993 | 1993 | 1993 | 1993 | 1993 |
| UN proper shipping name | FLAMMABLE LIQUIDS, N.O. S. (Isopropyl alcohol, n-butyl acetate) | FLAMMABLE LIQUIDS, N.O. S. (Isopropyl alcohol, n-butyl acetate) | FLAMMABLE LIQUIDS, N.O. S. (Isopropyl alcohol, n-butyl acetate) | FLAMMABLE LIQUIDS, N.O. S. (Isopropyl alcohol, n-butyl acetate) | FLAMMABLE LIQUIDS, N.O. S. (Isopropyl alcohol, n-butyl acetate) | FLAMMABLE LIQUIDS, N.O. S. (Isopropyl alcohol, n-butyl acetate) |
| Transport hazard class(es) | 3  | 3  | 3   | 3   | 3   | 3  |
| Packing group | III | III | III | III | III | III |
| Environmental hazards | Yes. | Yes. | Yes. | Yes. | Yes. | No. |
| Additional information | - | - | - | Special provisions 640 (E) Tunnel code (D/E) | - | - |

Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not available.

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

U.S. Federal regulations : **TSCA 8(a) CDR Exempt/Partial exemption**: Not determined
United States inventory (TSCA 8b): Not determined.
Clean Water Act (CWA) 307: Chromium oxide greens
Clean Water Act (CWA) 311: n-butyl acetate

Clean Air Act Section 112 (b) Hazardous Air Pollutants (HAPs) : Listed

Clean Air Act Section 602 Class I Substances : Not listed

Clean Air Act Section 602 Class II Substances : Not listed

DEA List I Chemicals (Precursor Chemicals) : Not listed

SECTION 15: Regulatory Information

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

Star Nail International, Inc. SAFETY DATA SHEET
 PRODUCT NAME: Cuccio Colour Veneer- 2 am in Hollywood Date: August 18, 2015

DEA List II Chemicals (Essential Chemicals) : Not listed

SARA 302/304

Composition/information on ingredients

No products were found.

SARA 304 RQ : Not applicable.

SARA 311/312

Classification : Fire hazard
 Immediate (acute) health hazard
 Delayed (chronic) health hazard

Composition/information on ingredients

| Name | % | Fire hazard | Sudden release of pressure | Reactive | Immediate (acute) health hazard | Delayed (chronic) health hazard |
|--------------------------------|---------|-------------|----------------------------|----------|---------------------------------|---------------------------------|
| Polyurethane acrylate oligomer | 50 - 75 | No. | No. | No. | Yes. | No. |
| 2-hydroxyethyl methacrylate | 10 - 25 | No. | No. | No. | Yes. | No. |
| titanium dioxide | 0 - 10 | No. | No. | No. | No. | Yes. |
| TPO | 1 - 5 | No. | No. | No. | No. | Yes. |
| Butyl acetate | 1 - 5 | Yes. | No. | No. | Yes. | No. |
| Ethyl acetate | 1 - 5 | Yes. | No. | No. | Yes. | No. |
| D & C yellow #10 | 0 - 5 | No. | No. | No. | Yes. | No. |
| D & C black #2 | 0 - 1 | No. | No. | No. | No. | Yes. |

SARA 313

| | Product name | CAS number | % |
|--|-----------------|------------|-------------|
| Form R - Reporting requirements | Aluminum powder | - | Proprietary |
| Supplier notification | Aluminum powder | - | Proprietary |

SARA 313 notifications must not be detached from the SDS and any copying and redistribution of the SDS shall include copying and redistribution of the notice attached to copies of the SDS subsequently redistributed.

State regulations

- Massachusetts** : The following components are listed: TITANIUM DIOXIDE; ETHYL ACETATE; BUTYL ACETATE; glass; Aluminum powder; FD & C blue #1; Red iron oxide; Mica
- New York** : The following components are listed: Ethyl acetate; Butyl acetate
- New Jersey** : The following components are listed: TITANIUM DIOXIDE; TITANIUM OXIDE (TiO₂); ETHYL ACETATE; ACETIC ACID, ETHYL ESTER; n-BUTYL ACETATE; ACETIC ACID, BUTYL ESTER; Aluminum powder; Red iron oxide; Mica; D & C black #2
- Pennsylvania** : The following components are listed: TITANIUM OXIDE (TiO₂); ACETIC ACID ETHYL ESTER; ACETIC ACID, BUTYL ESTER; Aluminum powder; Red iron oxide; D & C black #2
- Canada inventory** : Not determined.

International regulations

- International lists** : **Australia inventory (AICS)**: Not determined.
China inventory (IECSC): Not determined.
Japan inventory: Not determined.
Korea inventory: Not determined.
Malaysia Inventory (EHS Register): Not determined.
New Zealand Inventory of Chemicals (NZIoC): Not determined.
Philippines inventory (PICCS): Not determined.
Taiwan inventory (CSNN): Not determined.

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

Chemical Weapons : Not listed
 Convention List Schedule
 I Chemicals
 Chemical Weapons : Not listed
 Convention List Schedule
 II Chemicals
 Chemical Weapons : Not listed
 Convention List Schedule
 III Chemicals

SECTION 16: ADDITIONAL REGULATORY INFORMATION

Hazardous Material Information System (U.S.A.)

| | |
|---------------------|---|
| Health | 2 |
| Flammability | 2 |
| Physical hazards | 1 |
| Personal protection | |

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Reprinted with permission from NFPA 704-2001, Identification of the Hazards of Materials for Emergency Response Copyright ©1997, National Fire Protection Association, Quincy, MA 02269. This reprinted material is not the complete and official position of the National Fire Protection Association, on the referenced subject which is represented only by the standard in its entirety.

Copyright ©2001, National Fire Protection Association, Quincy, MA 02269. This warning system is intended to be interpreted and applied only by properly trained individuals to identify fire, health and reactivity hazards of chemicals. The user is referred to certain limited number of chemicals with recommended classifications in NFPA 49 and NFPA 325, which would be used as a guideline only. Whether the chemicals are classified by NFPA or not, anyone using the 704 systems to classify chemicals does so at their own risk.

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

Star Nail International, Inc. SAFETY DATA SHEET
PRODUCT NAME: Cuccio Colour Veneer- 2 am in Hollywood Date: August 18, 2015

Preparation Date of SDS: August 18, 2015

DISCLAIMER: This SDS is intended to provide a brief summary of our knowledge and guidance regarding the use of this material. The information contained here has been compiled from sources considered by us to be dependable and is accurate to the best of the Company's knowledge. It is not meant to be an all-inclusive document on worldwide hazard communication regulations.

This information is offered in good faith. Each user of this material needs to evaluate the conditions of use and design and the appropriate protective mechanisms to prevent employee exposure, property damage or release to the environment. Star Nail International assumes no responsibility for injury to the recipient or third persons, or for any damage to any property resulting from misuse of the product.

Key to abbreviations : ATE = Acute Toxicity Estimate
BCF = Bioconcentration Factor
GHS = Globally Harmonized System of Classification and Labelling of Chemicals
IATA = International Air Transport Association
IBC = Intermediate Bulk Container
IMDG = International Maritime Dangerous Goods
LogPow = logarithm of the octanol/water partition coefficient
MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

END OF SDS

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.

Star Nail International, Inc.

SAFETY DATA SHEET

PRODUCT NAME: Cuccio Colour Veneer- 2 am in Hollywood Date: August 18, 2015

UN = United Nations

The above information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty of merchantability, fitness for any use, or any other warranty is express or is to be implied regarding the accuracy of these data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material furnished on the condition that the person receiving it shall make his/her own determination as to the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.